

COPY

IN THE CLAIMS:

Applicant respectfully requests that the claims of the above-identified application be amended so as to read as follows thereby to place this application in condition for allowance, or at least in better form for Appeal, pursuant to 37 CFR 1.116:

1. (Currently Amended) An electrostatic suction type fluid discharge device, in which drive voltage supply means supplies a drive voltage between a nozzle and a discharge target and hence an electric charge is applied to a fluid supplied into the nozzle, so that the fluid is discharged as droplets from a hole of the nozzle to the discharge target,
the hole of the nozzle falling within a range between $\phi 0.01\mu\text{m}$ and $\phi 25\mu\text{m}$ in diameter, and
the drive voltage supply means outputting, as the drive voltage, a bipolar pulse voltage which has a frequency of not less than 1 Hz, and which alternates between positive and negative such that a positively charged fluid droplets and a negatively charged fluid droplets are alternately discharged in accordance with a polarity of the bipolar pulse voltage applied as the drive voltage and alternately landed on the discharge target.

COPY

2. (Currently Amended) An electrostatic suction type fluid discharge device, in which
- drive voltage supply means supplies a drive voltage between a nozzle and a discharge target and hence an electric charge is applied to a fluid supplied into the nozzle, so that the fluid is discharged as droplets from a hole of the nozzle to the discharge target,
- the hole of the nozzle falling within a range between $\phi 0.01\mu\text{m}$ and $\phi 25\mu\text{m}$ in diameter, and
- the drive voltage supply means outputting, as the drive voltage, a bipolar pulse voltage which alternates between positive and negative such that a positively charged fluid droplets and a negatively charged fluid droplets are alternately discharged in accordance with a polarity of the bipolar pulse voltage applied as the drive voltage and alternately landed on the discharge target, and which satisfies $f \leq 1/(2\tau)$ where τ is a time constant determined by $\tau = \epsilon/\sigma$, f is a drive voltage frequency (Hz), σ is an electric conductivity (S/m) of the discharge fluid, and ϵ is a relative permittivity of the discharge fluid.

COPY

3. (Currently Amended) An electrostatic suction type fluid discharge device, in which drive voltage supply means supplies a drive voltage between a nozzle and a discharge target and hence an electric charge is applied to a fluid supplied into the nozzle, so that the fluid is discharged as droplets from a hole of the nozzle to the discharge target, and the nozzle and the discharge target are moved in a relative manner by shifting means, in a direction orthogonal to a direction along which the nozzle and the discharge target oppose to each other,

the hole of the nozzle falling within a range between $\phi 0.01\mu\text{m}$ and $\phi 25\mu\text{m}$ in diameter,

the drive voltage supply means outputting, as the drive voltage, a bipolar pulse voltage which has a frequency of f Hz and which alternates between positive and negative such that a positively charged fluid droplets and a negatively charged fluid droplets are alternately discharged in accordance with a polarity of the bipolar pulse voltage applied as the drive voltage and alternately landed on the discharge target, and

the electrostatic suction type fluid discharge device further comprises ~~comprising~~ control means that controls at least one of the drive voltage supply means and the shifting means in such a manner as to satisfy $f \geq 5v$ where f is a drive voltage frequency (Hz) of the drive voltage supply means and v indicates a relative speed ($\mu\text{m}/\text{sec}$) of the relative movement of the nozzle and the discharge target.

4. (Currently Amended) An electrostatic suction type fluid discharge device, in which drive voltage supply means supplies a drive voltage between a nozzle and a discharge target and hence an electric charge is applied to a fluid supplied into the nozzle, so that the fluid is discharged as droplets from a hole of the nozzle to the discharge target, and the nozzle and the discharge target are moved in a relative manner by shifting means, in a direction orthogonal to a direction along which the nozzle and the discharge target oppose to each other,
- the hole of the nozzle falling within a range between $\phi 0.01\mu\text{m}$ and $\phi 25\mu\text{m}$ in diameter, and
- the drive voltage supply means outputting, as the drive voltage, a bipolar pulse voltage which is not more than 400V and which alternates between positive and negative such that a positively charged fluid droplets and a negatively charged fluid droplets are alternately discharged in accordance with a polarity of the bipolar pulse voltage applied as the drive voltage and alternately landed on the discharge target.

COPY

5. (Currently Amended) An electrostatic suction type fluid discharge method, in which a drive voltage is supplied between a nozzle and a discharge target and hence an electric charge is applied to a fluid supplied into the nozzle, so that the fluid is discharged as droplets from a hole of the nozzle to the discharge target, the hole of the nozzle falling within a range between $\phi 0.01\mu\text{m}$ and $\phi 25\mu\text{m}$ in diameter, and the drive voltage being a bipolar pulse voltage which has a frequency of not less than 1 Hz and alternates between positive and negative such that a positively charged fluid droplets and a negatively charged fluid droplets are alternately discharged in accordance with a polarity of the bipolar pulse voltage applied as the drive voltage and alternately landed on the discharge target.

COPY

6. (Currently Amended) An electrostatic suction type fluid discharge method, in which a drive voltage is supplied between a nozzle and a discharge target and hence an electric charge is applied to a fluid supplied into the nozzle, so that the fluid is discharged as droplets from a hole of the nozzle to the discharge target, the hole of the nozzle falling within a range between $\phi 0.01\mu\text{m}$ and $\phi 25\mu\text{m}$ in diameter, and the drive voltage being a bipolar pulse voltage which alternates between positive and negative such that a positively charged fluid droplets and a negatively charged fluid droplets are alternately discharged in accordance with a polarity of the bipolar pulse voltage applied as the drive voltage and alternately landed on the discharge target, and which satisfies $f \leq 1/(2\tau)$ where τ is a time constant determined by $\tau = \epsilon/\sigma$, f is a drive voltage frequency (Hz), σ is an electric conductivity (S/m) of the discharge fluid, and ϵ is a relative permittivity of the discharge fluid..

COPY

7. (Currently Amended) An electrostatic suction type fluid discharge method, in which a drive voltage is supplied between a nozzle and a discharge target and hence an electric charge is applied to a fluid supplied into the nozzle, so that the fluid is discharged as droplets from a hole of the nozzle to the discharge target, and the nozzle and the discharge target are moved in a relative manner, in a direction orthogonal to a direction along which the nozzle and the discharge target oppose to each other,

the hole of the nozzle falling within a range between $\phi 0.01\mu\text{m}$ and $\phi 25\mu\text{m}$ in diameter, as the drive voltage, a bipolar pulse voltage which has a frequency of f Hz being outputted and alternates between positive and negative such that a positively charged fluid droplets and a negatively charged fluid droplets are alternately discharged in accordance with a polarity of the bipolar pulse voltage applied as the drive voltage and alternately landed on the discharge target, and

at least one of the drive voltage frequency f Hz and a relative speed $v\mu\text{m}/\text{sec}$ of the relative movement of the nozzle and the discharge target being controlled in such a manner as to satisfy $f \geq 5v$.

COPY

8. (Currently Amended) An electrostatic suction type fluid discharge method, in which a drive voltage is supplied between a nozzle and a discharge target and hence an electric charge is applied to a fluid supplied into the nozzle, so that the fluid is discharged as droplets from a hole of the nozzle to the discharge target, the hole of the nozzle falling within a range between $\phi 0.01\mu\text{m}$ and $\phi 25\mu\text{m}$ in diameter, and the drive voltage being a bipolar pulse voltage which is not more than 400V and which alternates between positive and negative such that a positively charged fluid droplets and a negatively charged fluid droplets are alternately discharged in accordance with a polarity of the bipolar pulse voltage applied as the drive voltage and alternately landed on the discharge target.

COPY

9. (Currently Amended) An electrostatic suction type fluid discharge device that

(i) discharges, by electrostatic suction, a discharge fluid as droplets through a

Fluid discharge hole of a nozzle of a fluid discharge head, the

discharge fluid being electrically charged by voltage application,

and (ii) causes the discharge fluid to land onto a substrate, (iii) so

as to form a drawing pattern by the discharge fluid on a surface of
the substrate,

the fluid discharge hole of the nozzle falling in a range between $0.01\mu\text{m}$

and $25\mu\text{m}$ in diameter, and

the substrate being insulating,

the electrostatic suction type fluid discharge device comprising:

charge removal means for removing an electric charge on

the surface of the substrate, before the discharge

fluid is discharged onto the substrate; and

fluid discharge means for discharging the droplets of

discharge fluid onto the substrate from which the

electricity has been removed by a bipolar pulse

voltage which alternates between positive and

negative such that a positively charged fluid

droplets and a negatively charged fluid droplets are

alternately discharged in accordance with a polarity

of the bipolar pulse voltage applied as the drive

voltage and alternately landed on the substrate.

COPY

10. (Original) The electrostatic suction type fluid discharge device as defined in claim 9,
wherein, the charge removal means removes the electricity on the
substrate, in line with a predetermined pattern.
11. (Original) The electrostatic suction type fluid discharge device as defined in claim 9,
wherein, the fluid discharge means discharges the discharge fluid by
applying a voltage which is arranged such that an electric field
strength generated by electric charge concentration at a meniscus
part, when discharging the discharge fluid, is smaller than a
discharge start electric field strength figured out by an equation for
calculating Paschen curve.
12. (Original) The electrostatic suction type fluid discharge device as defined in claim 11,
wherein, the voltage applied when the fluid discharge means discharges
the discharge fluid is not less than 340V.
13. (Original) The electrostatic suction type fluid discharge device as defined in claim 11,
wherein, the fluid discharge hole of the nozzle is not less than 16 μ m or not
more than 0.25 μ m in diameter, and the voltage applied when the
fluid discharge means discharges the discharge fluid is not more
than 500V.

COPY

14. (Original) The electrostatic suction type fluid discharge device as defined in claim 11,
wherein, the fluid discharge hole of the nozzle is not less than $7.4\mu\text{m}$ or
not more than $0.65\mu\text{m}$ in diameter, and the voltage applied when
the fluid discharge means discharges the discharge fluid is not
more than 400V.

15. (Currently Amended) An electrostatic suction type fluid discharge method in which

(i) by electrostatic suction, a discharge fluid is discharged as droplets

through a fluid discharge hole of a nozzle of a fluid discharge

head, the discharge fluid being electrically charged by voltage

application, and (ii) the discharge fluid is droplets are caused to

land onto a substrate, (iii) so that a drawing pattern is formed by

the discharge fluid droplets on a surface of the substrate,

the fluid discharge hole of the nozzle falling in a range between $0.01\mu\text{m}$

and $25\mu\text{m}$ in diameter, and

the substrate being insulating, an electric charge on the surface of the

substrate being removed, before the discharge fluid is discharged

onto the substrate, and

the discharge fluid being discharged onto the substrate from which

electricity has been removed by a bipolar pulse voltage such that a

positively charged fluid droplets and a negatively charged fluid

droplets are alternately discharged in accordance with a polarity of

the bipolar pulse voltage applied as the drive voltage and caused to

alternately land on the substrate.

COPY

16. (Withdrawn) An electrostatic suction type fluid discharge device that

(i) discharges, by electrostatic suction, a discharge fluid through a fluid discharge hole of a nozzle of a fluid discharge head, the discharge fluid being electrically charged by voltage application, and (ii) causes the discharge fluid to land onto a substrate, (iii) so as to form a drawing pattern in accordance with desired patterning data by the discharge fluid on a surface of the substrate,

the fluid discharge hole of the nozzle falling in a range between $0.01\mu\text{m}$ and $25\mu\text{m}$ in diameter, and

the substrate being insulating, the electrostatic suction type fluid discharge device comprising:

electric charge providing means for providing an electric charge to a surface of the substrate, in line with a predetermined pattern.

COPY

17. (Withdrawn) The electrostatic suction type fluid discharge device as defined in claim 16,

wherein, the electric charge providing means provides the electric charge to an insulating substrate made of a photoconductive material, the electric charge providing means including:

uniform electric charging means for uniformly charging the surface of the insulating substrate; and

charge removal means for applying, in line with a predetermined pattern, a laser beam to the surface being uniformly charged, so as to remove electricity from a part of the surface where the laser beam has been applied.

18. (Withdrawn) An electrostatic suction type fluid discharge device that

(i) discharges, by electrostatic suction, a discharge fluid through a fluid discharge hole of a nozzle of a fluid discharge head, the discharge fluid being electrically charged by voltage application, and (ii) causes the discharge fluid to land onto a substrate, (iii) so as to form a drawing pattern in accordance with desired patterning data by the discharge fluid on a surface of the substrate,

the fluid discharge hole of the nozzle falling in a range between $0.01\mu\text{m}$ and $25\mu\text{m}$ in diameter, the substrate being insulating, and,

the electrostatic suction type fluid discharge device comprising:

voltage application means that is capable of touching the insulating substrate on which a pattern of a conductive material is formed and that applies a voltage to a conductive part on the insulating substrate, when the electrostatic suction type fluid discharge device discharges the discharge fluid.

COPY

19. (Withdrawn) A plot formation method using an electrostatic suction

type fluid discharge device that (i) discharges, by electrostatic suction, a discharge fluid through a fluid discharge hole of a nozzle of a fluid discharge head, the discharge fluid being electrically charged by voltage application, and (ii) causes the discharge fluid to land onto a substrate, (iii) so as to form a drawing pattern in accordance with desired patterning data by the discharge fluid on a surface of the substrate,

the fluid discharge hole of the nozzle falling in a range between $0.01\mu\text{m}$ and $25\mu\text{m}$ in diameter,

the substrate being insulating, before the discharge fluid is discharged, an electric charge, whose polarity is in reverse to a polarity of a drive voltage by which the discharge fluid is electrically charged in advance, being applied to a part of the insulating substrate where a drawing pattern is to be formed, so that an electric charge pattern is formed, and

the drawing pattern being formed by the discharge fluid, by discharging the discharge fluid on the electric charge pattern.

COPY

20. (Withdrawn) A plot formation method using an electrostatic suction

type fluid discharge device that (i) discharges, by electrostatic suction, a discharge fluid through a fluid discharge hole of a nozzle of a fluid discharge head, the discharge fluid being electrically charged by voltage application, and (ii) causes the discharge fluid to land onto a substrate, (iii) so as to form a drawing pattern in accordance with desired patterning data by the discharge fluid on a surface of the substrate,

the fluid discharge hole of the nozzle falling in a range between $0.01\mu\text{m}$ and $25\mu\text{m}$ in diameter,

the substrate being insulating, before the fluid is discharged, an electric charge, whose polarity is identical with a polarity of a drive voltage by which the discharge fluid is electrically charged in advance, being applied around a part on the insulating substrate where a drawing pattern is to be formed, so that an electric charge pattern is formed, and

the drawing pattern being formed by the discharge fluid, by discharging the discharge fluid onto a drawing pattern formation area which is surrounded by the electric charge pattern.

COPY

21. (Withdrawn) The plot pattern formation method as defined in claim 20, wherein,
the electric charge pattern is formed in such a manner that, after a
surface of the insulating substrate is electrically charged in a
uniform manner, a laser beam is applied to the uniformly-charged
surface in line with a predetermined pattern, and electricity is
removed from a part where the laser beam has been applied.
22. (Withdrawn) A plot formation method using an electrostatic suction
type fluid discharge device that (i) discharges, by electrostatic suction,
a discharge fluid through a fluid discharge hole of a nozzle of a
fluid discharge head, the discharge fluid being electrically charged
by voltage application, and (ii) causes the discharge fluid to land
onto a substrate, (iii) so as to form a drawing pattern in accordance
with desired patterning data by the discharge fluid on a surface of
the substrate,
the fluid discharge hole of the nozzle falling in a range between 0.01 μ m
and 25 μ m in diameter,

the substrate being insulating, before the discharge fluid is discharged,
an electric charge, whose polarity is identical with a polarity of a
drive voltage by which the discharge fluid is electrically charged in
advance, being applied to a non-image-drawing area where a
drawing pattern is not to be formed on the insulating substrate, so
that an electric charge pattern is formed, and
the drawing pattern being formed while the voltage applied for
discharging the discharge fluid is not stopped even on the non-
image drawing area.

23. (Withdrawn) A plot formation method using an electrostatic suction

type fluid discharge device that (i) discharges, by electrostatic suction,
a discharge fluid through a fluid discharge hole of a nozzle of a
fluid discharge head, the discharge fluid being electrically charged
by voltage application, and (ii) causes the discharge fluid to land
onto a substrate, (iii) so as to form a drawing pattern in accordance
with desired patterning data by the discharge fluid on a surface of
the substrate,

the fluid discharge hole of the nozzle falling in a range between $0.01\mu\text{m}$
and $25\mu\text{m}$ in diameter,

the substrate being insulating, and

in a case where a first drawing pattern made of a conductive
material has been formed by a conductive material on the
insulating substrate and a second drawing pattern is further formed
on the first drawing pattern, the second drawing pattern being
formed while a voltage is applied to the conductive part by which
the first drawing pattern is made.